



***Society of Cable
Telecommunications
Engineers***

**ENGINEERING COMMITTEE
Interface Practices Subcommittee**

AMERICAN NATIONAL STANDARD

ANSI/SCTE 124 2006

Specification for “F” Connector, Male, Pin Type

NOTICE

The Society of Cable Telecommunications Engineers (SCTE) Standards are intended to serve the public interest by providing specifications, test methods and procedures that promote uniformity of product, interchangeability and ultimately the long term reliability of broadband communications facilities. These documents shall not in any way preclude any member or non-member of SCTE from manufacturing or selling products not conforming to such documents, nor shall the existence of such standards preclude their voluntary use by those other than SCTE members, whether used domestically or internationally.

SCTE assumes no obligations or liability whatsoever to any party who may adopt the Standards. Such adopting party assumes all risks associated with adoption of these Standards, and accepts full responsibility for any damage and/or claims arising from the adoption of such Standards.

Attention is called to the possibility that implementation of this standard may require the use of subject matter covered by patent rights. By publication of this standard, no position is taken with respect to the existence or validity of any patent rights in connection therewith. SCTE shall not be responsible for identifying patents for which a license may be required or for conducting inquiries into the legal validity or scope of those patents that are brought to its attention.

Patent holders who believe that they hold patents which are essential to the implementation of this standard have been requested to provide information about those patents and any related licensing terms and conditions. Any such declarations made before or after publication of this document are available on the SCTE web site at <http://www.scte.org>.

All Rights Reserved

© Society of Cable Telecommunications Engineers, Inc.
140 Philips Road
Exton, PA 19341

TABLE OF CONTENTS

1.0	SCOPE	1
2.0	DEFINITIONS AND ACRONYMS.....	1
3.0	NORMATIVE REFERENCES.....	1
4.0	INFORMATIVE REFERENCES	2
5.0	ELECTRICAL REQUIREMENTS.....	3
6.0	MECHANICAL REQUIREMENTS	3

LIST OF FIGURES

FIGURE 1 – RECOMMENDED MALE “F” PIN TYPE CONNECTOR DRAWING	4
--	---

LIST OF TABLES

TABLE 1 – RECOMMENDED MALE “F” PIN TYPE CONNECTOR DIMENSIONS	4
--	---

1.0 SCOPE

The purpose of this document is to specify requirements for male “F” pin type connectors that are used in the 75 ohm RF broadband communications industry. This specification applies to SCTE drop cable specifications ANSI/SCTE 74 2003, ANSI/SCTE 71 2003, ANSI/SCTE 100 2004, IPS SP 005 and IPS SP 006.

All requirements of this document are measured after installation per manufactures instructions of the cable into the connector.

2.0 DEFINITIONS AND ACRONYMS

- 2.1 Dielectric: The material that is used to insulate the center conductor from contacting the outer housing.
- 2.2 Thread Relief: A reduced diameter section of the threaded surface to allow the tool to run out. This feature is optional.
- 2.3 Center Conductor: The pin conductor inside the male “F” pin type connector that accepts the coaxial cable center conductor.
- 2.4 Reference Plane: The reference plane on the male “F” pin type connector is the mating surface that seats against the female “F” port. It is also the plane from where all horizontal dimensions are taken.
- 2.5 Parting Line (relevant to casting process only): A raised mark left on the surface of a part as a result of the gap between two halves of a die.

3.0 NORMATIVE REFERENCES

The following documents contain provisions, which, through reference in this text, constitute provisions of this standard. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreement based on this standard are encouraged to investigate the possibility of applying the most recent editions of the documents listed below.

3.1 SCTE References

ANSI/SCTE 60 2004 (formerly IPS TP 013), Test Method for Interface Moisture Migration

ANSI/SCTE 74 2003 (formerly IPS SP 001), Specification for Braided 75 Ohm Flexible RF Coaxial Drop Cable

ANSI/SCTE 71 2003 (formerly IPS SP 004), Specification for Braided, 75 Ohm, Coaxial Multi-Purpose Cable

ANSI/SCTE 98 2004 (formerly IPS TP 400), Test Method for Withstand Tightening Torque - 'F' Male

ANSI/SCTE 99 2004 (formerly IPS TP 401), American National Standard Test Method for Axial Pull Connector/Cable

ANSI/SCTE 100 2004 (formerly IPS SP 007, Specification for 75 Ohm Smooth Aluminum Access Cables

ANSI/SCTE 103 2004 (formerly IPS TP 405), Test Method for DC Contact Resistance

IPS SP 005, Specification for Corrugated Copper 75 Ohm RF Coaxial Subscriber Access Cable

IPS SP 006, Specification for Corrugated Aluminum 75 Ohm RF Coaxial Subscriber Access Cable

IPS SP 400, Specification for “F” Port, Female, Outdoor

IPS SP 406, Specification for “F” Port, Female, Indoor

IPS TP 406, Test Method for Salt Spray

3.2 Standards from other Organizations—Not applicable.

4.0 INFORMATIVE REFERENCES

The following documents may provide valuable information to the reader but are not required when complying with this standard.

- 4.1 SCTE References—Not applicable.
- 4.2 Standards from other Organizations—Not applicable.
- 4.3 Published Materials—Not applicable.

5.0 ELECTRICAL REQUIREMENTS

- 5.1 Impedance: The male “F” pin type connector shall perform with a nominal impedance of 75 ohms.
- 5.2 Return Loss: Please see equipment specifications that the male “F” pin type connector is a part of for specific return loss requirements.
- 5.3 The outer conductor junction of the female F port to male “F” pin type connector shall have a DC contact resistance less than 10 milliohms when tightened to 35 in.-lbs. and tested to ANSI/SCTE 103 2004.
- 5.4 The center conductor junction of the female F port to male “F” pin type center conductor shall be capable of carrying a minimum of 1 Amp DC continuous current at an ambient temperature of 40°C without degradation.
- 5.5 Shielding Effectiveness: The shielding effectiveness for male “F” pin type connectors, when attached to cables manufactured to SCTE approved standards, shall meet shielding performance levels of an unspliced section of the same cable when both are tested with the same method.

6.0 MECHANICAL REQUIREMENTS

- 6.1 Physical dimensions

The recommended physical dimensions for the male “F” pin type connector shall be as specified in Figure 1, Table 1, and per the notes below.

NOTES

- 1 DIELECTRIC MUST NOT PROTRUDE BEYOND REF. PLANE.
- 2 THE MATING OF THE FEMALE 'F' TO THE REFERENCE PLANE SHOULD NOT BE IMPEDED.
- 3 MINIMUM ONE THREAD LEAD-IN.
- 4 RADIUS OPTIONAL.
- 5 DRAWING NOT TO SCALE.
- 6 INTERPRET DRAWING IN ACCORDANCE WITH ASME Y14.5M-1994.

6.2 Mechanical Strength

- 6.2.1 Withstand Tightening Torque: The male "F" pin type connector shall withstand a minimum tightening torque of 60 in-lbs. without damage when measured per ANSI/SCTE 98 2004, Test Method For Withstand Tightening Torque – 'F' Male.
- 6.2.2 Axial Pull Force: The male "F" pin type connector , when attached to cables manufactured to SCTE approved standards, shall withstand a minimum axial pull force of 40 lbs. for outdoor and 30 lbs. for indoor applications when tested per ANSI/SCTE 99 2004, Test Method For Axial Pull Connector/Drop Cable.

6.3 Outdoor Environmental Requirements

- 6.3.1 Male "F" pin type connectors shall meet the environmental requirements of the equipment to which they are attached and the requirements specified in this document.
- 6.3.2 Interface Moisture Migration: Male "F" pin type connectors, when attached to cables manufactured to SCTE approved standards, shall have no penetrant present or evident, when inspected visually, after undergoing testing per ANSI/SCTE 60 2004, Interface Moisture Migration Test.
- 6.3.3 Salt Spray: Male "F" pin type connectors shall be exposed to 1000 hours min. continuous salt spray per IPS-TP-406, Test Method For Salt Spray.

