

SCTE • ISBE[®]

S T A N D A R D S

Interface Practices Subcommittee

SCTE STANDARD

SCTE 51 2018

**Method for Determining
Drop Cable Braid Coverage**

NOTICE

The Society of Cable Telecommunications Engineers (SCTE) / International Society of Broadband Experts (ISBE) Standards and Operational Practices (hereafter called “documents”) are intended to serve the public interest by providing specifications, test methods and procedures that promote uniformity of product, interchangeability, best practices and ultimately the long-term reliability of broadband communications facilities. These documents shall not in any way preclude any member or non-member of SCTE•ISBE from manufacturing or selling products not conforming to such documents, nor shall the existence of such standards preclude their voluntary use by those other than SCTE•ISBE members.

SCTE•ISBE assumes no obligations or liability whatsoever to any party who may adopt the documents. Such adopting party assumes all risks associated with adoption of these documents, and accepts full responsibility for any damage and/or claims arising from the adoption of such documents.

Attention is called to the possibility that implementation of this document may require the use of subject matter covered by patent rights. By publication of this document, no position is taken with respect to the existence or validity of any patent rights in connection therewith. SCTE•ISBE shall not be responsible for identifying patents for which a license may be required or for conducting inquiries into the legal validity or scope of those patents that are brought to its attention.

Patent holders who believe that they hold patents which are essential to the implementation of this document have been requested to provide information about those patents and any related licensing terms and conditions. Any such declarations made before or after publication of this document are available on the SCTE•ISBE web site at <http://www.scte.org>.

All Rights Reserved

© Society of Cable Telecommunications Engineers, Inc.

140 Philips Road

Exton, PA 19341

TABLE OF CONTENTS


1.0	SCOPE	4
2.0	DEFINITIONS	4
3.0	BRAID COVERAGE FORMULA	4
4.0	BRAID COVERAGE EXAMPLE.....	5

1.0 SCOPE

This document is identical to SCTE 51 2012 except for informative components which may have been updated such as the title page, NOTICE text, headers and footers. No normative changes have been made to this document.

The purpose of this document is to provide instruction on the calculation of braid coverage for braided coaxial drop cables. Braid coverage is expressed as a percentage of optical coverage of the underlying core by the braid wires. It is a function of the diameter of the cable core, the diameter of the wire braid, the number of carriers (groups of wire ends), the number of individual wires in each carrier and the picks per inch (distance between each carrier crossing.)

2.0 DEFINITIONS



α = Braid angle (radians) - the angle formed by the carriers with the longitudinal axis of the cable (refer to the illustration)

D = Diameter under the braid (inches)

C = Number of carriers - the number of groups of individual braid wires (ends), usually 16 for most cable telecommunications braided cables (refer to the illustration)

d = Braid strand diameter (inches)

P = Picks per inch – the number of carrier crossing points per longitudinal inch (refer to the illustration)

N = Number of individual wires (ends) in each carrier

3.0 BRAID COVERAGE FORMULA

$$\text{Percent Braid Coverage} = (2 \cdot F - F^2) \times 100$$

where:

$$F = N \cdot P \cdot d / \sin \alpha$$

$$\alpha = \tan^{-1} [2 \cdot \pi \cdot (D + 2 \cdot d)(P/C)]$$

4.0 BRAID COVERAGE EXAMPLE

Cable construction: 59 Series, tape and braid construction

Given:

$D = 0.150$ inches (from measurement or ANSI/SCTE 74 2011)

$C = 16$ (from measurement)

$d = 0.0063$ (from measurement or ANSI/SCTE 74 2011)

$P = 6.0$ (from measurement)

$N = 4$ (from measurement)

$$\alpha = \tan^{-1} [2 \cdot \pi \cdot (0.150 + 2 \cdot 0.0063) \cdot (6.0/16)] = \tan^{-1} (0.383) = 0.366$$

$$F = 4 \cdot 6.0 \cdot 0.0063 / \sin (0.366) = 0.151 / 0.357 = 0.423$$

$$\text{Percent Braid Coverage} = (2 \cdot 0.423 - 0.423^2) \cdot 100 = 66.7\%$$